

Products name: AUKLET-KT88

**Integrated Tube Amplifier**



**Products Parametric**

Power Tube: KT88 x 4 / Impulse Tube: 6SN7 x 2 / Voltage Tube: 12AX7 x 2

Commute tube: 12AU7 x 2

Working state: class A,push-pull

Bias voltage state: Regular bias(Regulate outside)

Rated FULL-POWER Bandwidth: 8Ω/4Ω 45w 20Hz-30kHz -1dB

Maximum Continuous Power into 4-8 ohms: 60w

Rated Output Power THD: 45w/2%

Output Load impedance: 4ohms / 8 ohms

SNR: 89dB

Input Impedance at 1kHz: 100k or 20k
Input terminal: CD / AUX / LINE / PRE-INPUT
Max power ullage: 600VA
Product Size: (W)474mm x (D)385mm x (H)190mm
SNR: 89dB
Input Impedance at 1kHz: 100k or 20K
Input terminal: CD / AUX / LINE / PRE-INPUT
Max power ullage: 600VA
Weight: 32kgs
Accessory: Wire,Guide Instrument,Valve Pack,Guarantee Card,Remote control
CHARACTERISTIC: Gold socket / roast paint(black) / Red copper binding post / Wooden Panel / Manual Point To Point Welding / Perfect tubes packing

